



Braided glass fibre hose, heat class F (155°C) with polyurethane varnish, in accordance with DIN 60684-3

Braided Insulating Sleeves 14F

Technical specifications

Material:

Glas silk braid varnished with polyurethane coating

Temperature Class:

F (155°C)

Dielectric strength:

up to 6.0 mm 6 kV min.

from 7.0 mm 4 kV min.

Colors:

natural, other colors on request

Put-up:

0.3 - 4.0 mm Ø: rings of 200 m

4.5 - 16.0 mm Ø: rings of 100 m

from 18.0 mm Ø: in lengths of 1 meter

(Subject to changes)

Dimensions:

Article number		Inside Ø	Wall thickness		Article number		Inside Ø	Wall thickness		Article number		Inside Ø	Wall thickness
IS14F003	◆	0,3	0,4		IS14F045	◆	4,5	0,5		IS14F160	◆	16,0	1,0
IS14F005	◆	0,5	0,4		IS14F050	◆	5,0	0,6		IS14F180	◆	18,0	1,0
IS14F008	◆	0,8	0,4		IS14F060	◆	6,0	0,6		IS14F200	◆	20,0	1,0
IS14F010	◆	1,0	0,4		IS14F070	◆	7,0	0,7		IS14F220	◆	22,0	1,2
IS14F015	◆	1,5	0,4		IS14F080	◆	8,0	0,7		IS14F240	◆	24,0	1,2
IS14F020	◆	2,0	0,4		IS14F090	◆	9,0	0,7		IS14F260	◆	26,0	1,2
IS14F025	◆	2,5	0,4		IS14F100	◆	10,0	0,7		IS14F280	◆	28,0	1,2
IS14F030	◆	3,0	0,4		IS14F110	◆	11,0	0,7		IS14F300	◆	30,0	1,2
IS14F035	◆	3,5	0,4		IS14F120	◆	12,0	0,8					

◆ from stock

◆ On request

These hoses can also be supplied with UL approval. The specifications change compared to the standard version. Minimum order quantities apply depending on the diameter.