

Thanks to their outstanding quality, these Safety Thermal Protectors meet the highest safety and reliability requirements. They are equipped with a patented switching system that has been tried and tested millions of times.

Thermal Protectors / Stock Range

Standard range

Item number		Nominal switching temperature [˚C]	Nominal switching current [A]	Item number		Nominal switching temperature [˚C]	Nominal switching current [A]
Normally open				**Normally open**			
TWS01.080.0300	♦	80°C	2,5	**TWS06.090.0300**	♦	90°C	10
TWS01.090.0300	♦	90°C	2,5	**TWS06.100.0300**	♦	100°C	10
TWS01.100.0300	♦	100°C	2,5	**TWS06.110.0300**	♦	110°C	10
TWS01.110.0300	♦	110°C	2,5	**TWS06.120.0300**	♦	120°C	10
TWS01.120.0300	♦	120°C	2,5	**TWS06.130.0300**	♦	130°C	10
TWS01.130.0300	♦	130°C	2,5	**TWS06.140.0300**	♦	140°C	10
TWS01.140.0300	♦	140°C	2,5	**TWS06.150.0300**	♦	150°C	10
TWS01.150.0300	♦	150°C	2,5	**TWS06.160.0300**	♦	160°C	10
TWS01.155.0300	♦	155°C	2,5	**TWS06.170.0300**	♦	170°C	10
TWS01.160.0300	♦	160°C	2,5	**TWS06.180.0300**	♦	180°C	10
TWS01.170.0300	♦	170°C	2,5	**Normally closed**			
TWS01.180.0300.	♦	180°C	2,5	**TWS08.130.0300**	♦	130°C	10
TWS01.200.0300.	♦	200°C	2,5	**TWS08.140.0300**	♦	140°C	10
				TWS08.150.0300	♦	150°C	10

Standard cable length: 300 mm

♦ Stock types

♦ Available from factory stock, minimum quantity on request